IMPERIAL GRAY GRANITE DRYSTACK

SPECIFICATIONS

A traditional gray granite color in a contemporary, linear style with little to no joint exposed.

THIN VENEER

LENGTH 4" - 30" Random (12" Average)

HEIGHT* Sawn 2", 4", & 6

THICKNESS 3/4" - 1 1/2"

YIELD 10-15 lbs/ft²

*Typical height ratio: 20% = 2", 50% = 4", 30% = 6". Additional heights available upon request.

ASTM C-97 - ABSORPTION & BULK SPECIFIC GRAVITY

WATER ABSORPTION .09%
BULK SPECIFIC GRAVITY 2.672

ASTM C-170 - COMPRESSIVE STRENGTH

PARALLEL TO RIFT DRY 34,280 psi
PARALLEL TO RIFT, WET 29,460 psi
PERPENDICULAR TO RIFT, DRY 32,750 psi
PERPENDICULAR TO RIFT, WET 31,770 psi

ASTM C-99 - MODULUS OF RUPTURE

PARALLEL TO RIFT DRY
2,410 psi
PARALLEL TO RIFT, WET
1,910 psi
PERPENDICULAR TO RIFT, DRY
2,540 psi
PERPENDICULAR TO RIFT, WET
2,060 psi

ASTM C-880 - FLEXURAL STRENGTH

PARALLEL TO RIFT DRY 2,440 psi
PARALLEL TO RIFT, WET 2,150 psi
PERPENDICULAR TO RIFT, DRY 2,510 psi
PERPENDICULAR TO RIFT, WET 2,050 psi



